

Fleet **POWERGARD**™

PREMIUM COOLANTS



HEAVY DUTY MIXED FLEET LIFETIME ANTIFREEZE/COOLANT PRE-MIX 50/50

PowerGard™ Fleet Heavy Duty Antifreeze/Coolant is a Nitrite, Amine, Phosphate, Borate, Molybdate and Silicate free Polyorganic coolant. This is sometimes referred to as a NAPS Free coolant and if properly maintained will likely last the life of your diesel engine or passenger vehicle.*

ADVANTAGES

- Will provide up to 750,000 miles or 6 years of service life protection in heavy duty diesel use if properly maintained.
- Fully compatible with other OAT extended life coolants as long as they meet ASTM standards.
- A preferred choice where mixed fleets or light duty and heavy duty applications are needed.
- No SCA's or chemical filters are needed. An added cost savings for end-users.**
- Designed for superior performance in wet sleeve liner cavitation protection, as well as corrosion/erosion protection of all metals.
- Blended with pure De-ionized water
- Includes bittering agent in all packages meeting all North American acceptable ranges.



* Must be properly maintained per manufacturer's instructions and or ORG ChemGroup instructions.

** Blank filters without chemistry content are acceptable.

Fleet **POWERGARD**[™] PREMIUM COOLANTS

PowerGard[™] Fleet will provide outstanding performance in the following applications:

- Case New Holland[™]
- Caterpillar[™]
- Chrysler[™]
- Cummins[™]
- Detroit Diesel[™]
- Ford[™]
- Freightliner[™]
- GM Dex-Cool[™]
- GMC Truck[™]
- International Truck[™]
- John Deere[™]
- Kenworth[™]
- Mack Trucks[™]
- Navistar[™]
- Paccar[™]
- Peterbilt[™]
- Thermo-King[™]
- Volvo[™]

Chemical inhibitors in PowerGard[™] Fleet meet the following:

- ASTM 6210
- ASTM 3306
- US Military A-A 52624-A
- TMC RP 329

PowerGard[™] Fleet is Phosphate and Silicate free to satisfy the requirements of European and Japanese OEM's.

TYPICAL PROPERTIES

DESCRIPTION	TEST NUMBER	VALUE
Specific gravity	D-1122	1.231
Freeze Point 50% B/V	D-3321 or D-1177	-34' F
Boiling Point 50% B/V	D-1120	265' F – 15# Cap
Reserve Alkalinity	D-1121	5.5
Foam Test	D-1881	80 ml / 2.0 sec max
Color	Visual	Yellow or Red

Available in Drums, Totes, Bulk and Gallon Jugs



Are Trademarks of ORG Chem-Group, LLC



11210 Solomon Road
Troy, In, 47588
812.547.7951